

Bench Mounted



	KCS-TF1/E	KCS-TF2/E	KCS-TF3/E	KCS-TF4/E
Max. Capacity 1-2 Wire Braided (in)	1 1/4	2	2	3
Max. Capacity 4 Spiral (in)	1 1/4	2	2	3
Max. Capacity 6 Spiral (in)	1	1 1/2	2	2
Max. Capacity Industrial (in)	2	2	2 1/2	4
Max. Opening (mm / in)	60 / 2.36	75 / 2.95	85 / 3.35	130 / 5.12
Blade Diameter (mm)	250	250	350	400
Power	1.5 HP (110 V)	4.0 HP (230 V)	4.0 HP (230 V)	5.5 HP (230 V)
Page Number	49	50	51	52

Stand Alone



	KCS-TF2	KCS-TF3	KCS-TF3/PI	KCS-TF4	KCS-TF5
Max. Capacity 1-2 Wire Braided (in)	2	3	3	3	3
Max. Capacity 4 Spiral (in)	2	2 1/2	2 1/2	2 1/2	2 1/2
Max. Capacity 6 Spiral (in)	1 1/2	2	2	2	2 1/2
Max. Capacity Industrial (in)	2	2 1/2	2 1/2	3	5*
Max. Opening (mm / in)	75 / 2.95	100 / 3.94	100 / 3.94	100 / 3.94	160 / 6.30
Blade Diameter (mm)	250	400	400	400	520
Power	4 HP (110 V)	7.5 HP (230 V)	7.5 HP (230 V)	7.5 HP (230 V)	10.0 HP (230 V)
Powered Foot Pedal	No	No	Yes	Yes	Yes
Low Smoke Emission	No	No	No	Yes	Yes
Page Number	53	54	55	56	57

* Dependent on hose type

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.