

# **Standard Volume Crimpers**

Hose Capacity (in)		Crimping Force (ton)
1 – 2 Wire	2	
4 SP / 6 SP	2 / 2*	200
90° Fittings	2	<b>308</b>
Industrial	<b>4</b> <sup>†</sup>	

\*2" limited to 5,000 PSI hose using 1-pc fittings <sup>†</sup>Up to 5" depending on hose and coupling type

Opening Diameter	
Max. Without Dies (mm / in)	219 / 8.62
Max. With Dies (mm / in)	192 / 7.56
By Die Size (mm / in)	Die Size + <b>61 / 2.42</b>

Crimper Size	
LxWxH(in)	32.3 x 25.9 x 33.0
Weight (lbs)	1,102

Part Number	Motor Info
KC3-H170-230/3	7 HP (230 V) 3 PH

Die Series	Die Range (mm)
H119 & H144	6 – 131*

<sup>\*</sup> Custom Dies available to 138 mm

### Refer to pg. 20 for available dies

#### **Control Mechanism:**



ES3

- Full-color, touch-screen display
- Stores up to 200 crimp specifications
- Built-in crimp diameter calculator
- Adjustable reopen diameter
- USB port option for data transfer

## KC3-H170 Series






**Description:** The widest opening of all the Standard Volume Crimpers makes this crimper ideal for industrial hose. It makes an excellent hydraulic hose crimper as well, handling up to 2" wire braid and 4 SP hose, along with our 6 SP hoses up to 5000 PSI using F Series, 1-piece fittings. Reduction dies included.

### **Included Accessories:**







Crimp Calculator

### Optional Accessories: (pgs. 34 - 41)



Quick Change Die Tool KCQCT-H119



Patented Quick Change Die Tool KCPQCT-H170



Die Holder Base (18 pc.) DIEBASE-H119




Die Rack (8 pc.) DIERACK-H119



Electric Foot Pedal PEDAL-ES



ES3 Upgrades (pg. 35)



**Back Mirror** MIRROR-H135/170



Cleaning and Lubrication Kit CALKIT-H144/170



**Custom Made Dies** (pg. 41)



Marking Dies (pg. 41)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

